



# 04000AC Motor Oil 15W-40 Extra High Performance Diesel Truck

Document version: 4 October 2015



Art. no.	Volume	Items per unit	Items per pallet
04020AC	20 L	1	30
04060AC	60 L	1	12
04205AC	205 L	1	2
04999AC	1000 L	1	0
P04000AC	bulk	1	0

## Description

This Extra High Performance Diesel motor oil (ACEA E9) has been specially developed for use in the modern, high output, low emission engines of commercial vehicles according to Euro 4 and Euro 5 emission standards and also gives excellent protection in older diesel engines. Important: This motor oil is absolutely not suitable for use in petrol engines.

## Specifications

ACEA E9/E7  
API CJ-4/CI-4+/CI-4/SM/CF  
Caterpillar ECF-2 / ECF-3  
Cummins CES 20081  
Global DHD-1  
JASO DH-1 / DH-2  
Mack EO-O  
MAN M 3275  
MB-Approval 228.31  
MTU Type 2

Renault RLD-3  
Volvo VDS-4 / VDS-3

Typical characteristics

Density at 15°C	0,870	kg/l
Kinematic viscosity at 40°C	113.0	mm <sup>2</sup> /s
Kinematic viscosity at 100°C	13.8	mm <sup>2</sup> /s
Viscosity index	139	
Dynamic viscosity at -20°C	6400	mPa·s
Flashpoint COC	225	°C
Pourpoint	-36	°C
Total Base number	8.0	mgKOH/g
Sulphated ash	1.0	mass%