



## 04000HM Motor Oil 10W-40 Semi Synthetic Higher Mileage

Document version: 5 November 2015



| Art. no. | Volume | Items per unit | Items per pallet |
|----------|--------|----------------|------------------|
| 04001HM  | 1 L    | 6              | 450              |
| 04005HM  | 5 L    | 4              | 112              |
| 04020HM  | 20 L   | 1              | 30               |
| 04060HM  | 60 L   | 1              | 12               |
| 04205HM  | 205 L  | 1              | 2                |
| 04999HM  | 1000 L | 1              | 0                |
| P04000HM | bulk   | 1              | 0                |

### Description

This motor oil has been specially developed to delay the ageing process as well as oil leaks through cracked rings, oxidation and a higher fuel consumption in engines with a high mileage and as a result to extend the engine life.

### Specifications

API SL/CF

## Typical characteristics

|                              |       |                    |
|------------------------------|-------|--------------------|
| Density at 15°C              | 0,881 | kg/l               |
| Kinematic viscosity at 40°C  | 97.0  | mm <sup>2</sup> /s |
| Kinematic viscosity at 100°C | 14.1  | mm <sup>2</sup> /s |
| Viscosity index              | 150   |                    |
| Dynamic viscosity at -25°C   | 6000  | mPa·s              |
| Flashpoint COC               | 220   | °C                 |
| Pourpoint                    | -39   | °C                 |
| Total Base number            | 7.9   | mgKOH/g            |
| Sulphated ash                | 1.0   | mass%              |
| Noack evaporation loss       | 12.8  | mass%              |