



05000A Motor Oil 10W-40 Premium Synthetic Diesel

Document version: 2 October 2015



Art. no.	Volume	Items per unit	Items per pallet
05001A	1 L	6	450
05005A	5 L	4	112
05020A	20 L	1	30
05060A	60 L	1	12
05205A	205 L	1	2
05999A	1000 L	1	0
P05000A	bulk	1	0

Description

This MPM Motor Oil 10W-40 Premium Synthetic Diesel is a fully synthetic engine oil. It provides superior protection for most Euro IV, Euro V and the latest Scania Euro VI high performance diesel engines. Recommended in a wide range of heavy duty applications, suitable for on-road and off-road transport, construction and agricultural industries.

This 'long-drain' oil is specially developed for Scania engines which require the LDF-3 specification.

Specifications

ACEA E4/E7
API CF
Cummins CES 20072
Deutz DQC III-10
Mack EO-N
MAN M 3277
MB-Approval 228.5
MTU Type-3

Renault RXD/RD-2/RLD/RLD-2

Scania LDF-2

Scania LDF-3

Volvo VDS-3

Typical characteristics

SAE	10W-40	
Density at 15°C	0,870	kg/l
Kinematic viscosity at 40°C	86,3	mm ² /s
Kinematic viscosity at 100°C	13,3	mm ² /s
Viscosity index	155	
Flashpoint COC	220	°C
Pourpoint	-39	°C
Total Base number	16,1	mgKOH/g