



05000 Motor Oil 5W-40 Premium Synthetic

Document version: 7 October 2015



Art. no.	Volume	Items per unit	Items per pallet
05001	1 L	6	450
05004	4 L	4	112
05005	5 L	4	112
05020	20 L	1	30
05060	60 L	1	12
05205	205 L	1	2
05999	1000 L	1	0
P05000	bulk	1	0

Description

This very marketable universal premium synthetic motor oil of top quality has been specially developed for modern petrol and diesel engines in cars and delivery vans and meets the requirements of all leading car manufacturers.

Specifications

ACEA A3/B4
API SN / CF
BMW LL-01
MB-Approval 229.3
Opel GM-LL-B-025
Porsche A40
PSA B71 2296
Renault RN0710 / RN0700
VW 502.00 / 505.00

Typical characteristics

Density at 15°C	0,856	kg/l
Kinematic viscosity at 40°C	86,0	mm ² /s
Kinematic viscosity at 100°C	14,4	mm ² /s
Viscosity index	175	
Dynamic viscosity at -30°C	6100	mPa·s
Flashpoint COC	220	°C
Pourpoint	-42	°C
Total Base number	9,6	mgKOH/g
Sulphated ash	1,2	mass%
High Temperature / High Share	0	mPa·s
Noack evaporation loss	0	mass%