



35000 STOU 10W-30 GL-4 Multitrac Mineral

Document version: 2 December 2015



Art. no.	Volume	Items per unit	Items per pallet
35001	1 L	6	450
35005	5 L	4	112
35020	20 L	1	30
35060	60 L	1	12
35205	205 L	1	2
35999	1000 L	1	0
P35000	bulk	1	0

Description

This high-grade mineral STOU (Super Tractor Oil Universal) Multitrac 10W-30 multifunctional agricultural oil has been specially developed for use in diesel engines, transmissions, power take-off, wet brakes, hydraulic systems, power steering and end drive of among others tractors, combines, road building and hydraulic engineering machines.

Specifications

Allison C4
API CF-4/GL-4
Caterpillar TO-2
Ford M2C 86A / 134C / 159
John Deere JD14B / JD 20A/C / J27
Massey Ferguson M-1135 / M-1139 / M-1143 / M-1144
MIL-L-46152C / 2104D / 2105
ZF TE-ML-06 / 07

Typical characteristics

Density at 15°C	0,881	kg/l
Kinematic viscosity at 40°C	75.0	mm ² /s
Kinematic viscosity at 100°C	11.4	mm ² /s
Viscosity index	144	
Dynamic viscosity at -25°C	6700	mPa·s
Flashpoint COC	216	°C
Pourpoint	-35	°C
Total Base number	10.7	mgKOH/g