



36000 STOU 15W-30 GL-4 Multitrac Mineral

Document version: 2 December 2015



Art. no.	Volume	Items per unit	Items per pallet
36001	1 L	6	450
36005	5 L	4	112
36020	20 L	1	30
36060	60 L	1	12
36205	205 L	1	2
36999	1000 L	1	0
P36000	bulk	1	0

Description

This high-grade mineral STOU (Super Tractor Oil Universal) Multitrac 15W-30 multifunctional agricultural oil has been specially developed for use in diesel engines, transmissions, power take-offs, wet brakes, hydraulic systems, power steering and end drive of among others tractors, combines, road and hydraulic engineering machines.

Specifications

Allison C4
API CF-4/GL-4
Caterpillar TO-2
Ford M2C-86A / 134C/D / 159B/C
John Deere JD14B / JD 20A/C / J27
Massey Ferguson M-1135 / M-1139 / M-1143 / M-1144 / M-1127A / M-1129A
MIL-L-46152C / 2104D / 2105
ZF TE-ML 06A&B / 07B

Typical characteristics

Density at 15°C	0,887	kg/l
Kinematic viscosity at 40°C	81.7	mm ² /s
Kinematic viscosity at 100°C	10.8	mm ² /s
Viscosity index	118	
Dynamic viscosity at -20°C	6600	mPa·s
Flashpoint COC	222	°C
Pourpoint	-35	°C
Total Base number	10.7	mgKOH/g