

37000 UTTO GL-4 Mineral

Document version: 25 October 2015



Art. no.	Volume	Items per unit	Items per pallet
37001	1 L	6	450
37005	5 L	4	112
37020	20 L	1	30
37060	60 L	1	12
37205	205 L	1	2
37999	1000 L	1	0
P37000	bulk	1	0

Description

This mineral GL-4 UTTO (Universal Tractor Transmission Oil) transmission oil has been specially developed for tractors that need one lubrication oil for the hydraulic system, drive, differential, wet brakes and clutches.

Specifications

Allison C4
 API GL-4
 Case IH MS 1206 / MS 1207 / MS 1210
 Case New Holland MAT 3525 / 3505
 Ford New Holland M2C-134 C / D / FNHA-2-C-201.00
 John Deere J20 C/D
 Massey Ferguson M 1135 / M 1143 / M 1145
 Volvo Construction Equipment WB-101
 ZF TE-ML 03E / 03F / 05F / 06K

Typical characteristics

SAE	10W-30	
Density at 15°C	0,885	kg/l
Kinematic viscosity at 40°C	58,5	mm ² /s
Kinematic viscosity at 100°C	10	mm ² /s
Viscosity index	158	
Dynamic viscosity at -20°C	2900	mPa·s
Flashpoint COC	212	°C
Pourpoint	-39	°C
Total Base number	7,5	mgKOH/g