



43000 2-Stroke Oil Synthetic TC+

Document version: 1 October 2015



| Art. no. | Volume | Items per unit | Items per pallet |
|----------|--------|----------------|------------------|
| 43001 | 1 L | 6 | 450 |
| 43005 | 5 L | 4 | 112 |
| 43020 | 20 L | 1 | 30 |
| 43060 | 60 L | 1 | 12 |
| 43205 | 205 L | 1 | 2 |
| 43999 | 1000 L | 1 | 0 |

Description

This TC+ synthetic high-grade 2-stroke oil has been specially developed for use in modern air- and/or water-cooled 2-stroke engines. This 2-stroke oil is self-mixing and extremely suitable for engines with oil-injection systems.

Specifications

CEC/API:TC+
ISO-LEGD
JASO FC (low smoke)
Piaggio SI
TISI

Typical characteristics

| | | |
|------------------------------|-------------|--------------------|
| Density at 15°C | 0,882 | kg/l |
| Colour | Yellowbrown | |
| Kinematic viscosity at 40°C | 78.4 | mm ² /s |
| Kinematic viscosity at 100°C | 10.2 | mm ² /s |
| Viscosity index | 112 | |
| Flashpoint COC | 100 | °C |
| Pourpoint | -15 | °C |
| Total Base number | 1.1 | mgKOH/g |
| Sulphated ash | 0.28 | mass% |