



## 51000A Fork Oil Light 5W

Document version: 5 October 2015



Art. no.	Volume	Items per unit	Items per pallet
51001A	1 L	6	450
51020A	20 L	1	30
51060A	60 L	1	12
51205A	205 L	1	2
51999A	1000 L	1	0

### Description

This MPM high quality 5W Fork Oil is specially developed for use in telescopic forks and shock absorbers of road/off-road motorcycles and mopeds. This fork oil is produced with high quality mineral oils with high viscosity index. The high de-aeration properties of this MPM fork oil means that there is minimum/reduced foaming in the fork legs/shock absorber bodies. This gives optimal performance and stability not only for normal day to day use, but will maintain optimal performance under extreme road/off-road conditions. MPM 5W-Fork oil offers excellent protection against component wear and seal corrosion, thus resulting in increased longevity of the components.

Note: Can also be used in shock-absorbers and telescopic forks of mountain bikes and bicycles where the manufacturer specifies a 5W oil.

### Specifications

SAE 5W

## Typical characteristics

Density at 15°C	0,859	kg/l
Colour	Yellowbrown	
Kinematic viscosity at 40°C	15,4	mm <sup>2</sup> /s
Kinematic viscosity at 100°C	3,9	mm <sup>2</sup> /s
Viscosity index	155	
Flashpoint COC	180	°C
Pourpoint	-36	°C