



61000 MoS2 grease EP-2

Document version: 25 October 2015



| Art. no. | Volume | Items per unit | Items per pallet |
|----------|--------|----------------|------------------|
| 61000 | 0,4 kg | 12 | 1200 |
| 61500 | 0,5 kg | 6 | 864 |
| 61001 | 1 kg | 6 | 462 |
| 61005 | 5 kg | 1 | 90 |
| 61018 | 18 kg | 1 | 28 |
| 61050 | 50 kg | 1 | 12 |
| 61185 | 185 kg | 1 | 2 |

Description

This MoS2 EP grease has been specially developed for use under the most extreme load. This grease is extremely suitable for applications where high loads and low speeds of revolution are present. The addition of Molybdenum disulfide ensures very good lubrication, even after grease leaks due to excessive temperature increase.

Specifications

DIN 51502
ISO 673
ISO-L-XCC IB2
KP2K-30

Typical characteristics

| | | |
|-----------------------------|-----------|--------------------|
| Base oil | mineral | |
| Additive | Molybdeen | |
| Colour | Dark grey | |
| Kinematic viscosity at 40°C | 100 | mm ² /s |
| NLGI class | 2 | |
| Temperature range | -20 / 120 | °C |
| Soap thickener | Lithium | |