



65000H Heavy Duty Grease

Document version: 19 October 2015



| Art. no. | Volume | Items per unit | Items per pallet |
|----------|--------|----------------|------------------|
| 65000H | 0,4 kg | 12 | 1200 |
| 65001H | 1 kg | 6 | 462 |
| 65005H | 5 kg | 1 | 90 |
| 65018H | 18 kg | 1 | 28 |
| 65050H | 50 kg | 1 | 12 |
| 65185H | 185 kg | 1 | 2 |

Description

MPM Heavy Duty Grease is a high-performance Lithium-Calcium grease. This high quality mineral base oil in combination with special EP additives and polymers prevent metal-to-metal contact, reducing friction and wear under extreme conditions. It provides a stable and adherent lubricant film with outstanding water-resistance properties, even under high load conditions. MPM Heavy Duty Grease covers a wide range of usage including off-road and construction applications such as bucket pins, chassis points and heavily loaded plain bearings in shovel loaders and other equipment. It is also suitable for certain 2-way centralised lubrication systems and as fifth wheel grease.

Specifications

DIN 51825
KP2K-20

Typical characteristics

| | | |
|-----------------------------|-----------------|--------------------|
| Colour | green | |
| Kinematic viscosity at 40°C | 600 | mm ² /s |
| NLGI class | 2 | |
| Temperature range | -20 / 120 | °C |
| Peak temperature | 140 | °C |
| Soap thickener | Lithium-Calcium | |